

Foam-Control® R-SHIELD® is a film-faced air barrier and weather resistive insulation used for all types of construction applications. Foam-Control R-SHIELD conforms to ASTM C578, “Standard Specification for Rigid, Cellular Polystyrene Thermal Insulation”.

Foam-Control R-SHIELD is manufactured under an industry leading quality control program monitored by UL and further recognized in UL Evaluation Report UL ER11812-01.



| PRODUCT | | FOAM-CONTROL R-SHIELD™ | | | |
|--|--|--|---------------|---------------|---------------|
| | | 100 | 130 | 150 | 250 |
| Compressive Strength ^{1,2} @ 10% deformation, min. ASTM D1621 | psi (kPa) | 10 (69) | 13 (90) | 15 (104) | 25 (173) |
| R-value ¹ , Thermal Resistance, per inch, ASTM C518 | 25°F ³ | °F·ft ² ·h/Btu (°K·m ² /W) 4.4 (0.77) | 4.5 (0.80) | 4.8 (0.84) | 5.0 (0.88) |
| | 40°F ⁴ | °F·ft ² ·h/Btu (°K·m ² /W) 4.2 (0.74) | 4.3 (0.76) | 4.6 (0.81) | 4.8 (0.85) |
| | 75°F ⁵ | °F·ft ² ·h/Btu (°K·m ² /W) 3.9 (0.69) | 3.9 (0.69) | 4.2 (0.74) | 4.4 (0.77) |
| Density, Nominal ASTM C303 | lb/ft ³ (kg/m ³) | 1.0 (16) | 1.25 (20) | 1.5 (24) | 2.0 (32) |
| Flexural Strength ¹ , min. ASTM C203 | psi (kPa) | 25 (173) | 30 (208) | 35 (242) | 50 (345) |
| Water Vapor Permeance ¹ of 1.0 in. thickness, max., perm ASTM E96 | | 0.3 | 0.3 | 0.3 | 0.3 |
| Water Absorption ¹ by total immersion, max., volume % ASTM C272 | | <1.0 | <1.0 | <1.0 | <1.0 |
| Flame Spread ASTM E84 | | <25 | <25 | <25 | <25 |
| Smoke Developed ASTM E84 | | <450 | <450 | <450 | <450 |
| ASTM C578 Compliance, Type | | I | VIII | II | IX |

¹ Please refer to ASTM C578 specification for complete information.

² Compressive strength is measured at 10 percent in accordance with ASTM C578. A safety factor is required to prevent long-term creep for sustained loads. For static loads, a safety factor of 3:1 is recommended.

³ Recommended for design in EXTREME COLD climates.

⁴ Recommended for design in COLD climates.

⁵ Recommended for design in WARM climates.

Thermal Performance.

The R-value of Foam-Control R-SHIELD remains constant and does not suffer from R-value loss. The closed cell structure of Foam-Control R-SHIELD contains air and not blowing agents which deplete over time.

Exposure to Water and Water Vapor.

The mechanical properties of Foam-Control R-SHIELD are unaffected by moisture. Exposure to water or water vapor does not cause swelling.

Temperature Exposure/Flame Retardants.

Foam-Control R-SHIELD is able to withstand the rigors of temperature cycling, assuring long-term performance.

Although flame retardants used in the manufacture of Foam-Control R-SHIELD provide an important margin of safety, all Foam-Control R-SHIELD products must be considered combustible.

The maximum recommended long-term exposure temperature for Foam-Control R-SHIELD is 165°F (74°C).

Weathering.

Long-term exposure to sunlight causes yellowing and a slight embrittlement of the surface due to ultraviolet light. This has little effect on mechanical properties. If stored outdoors, cover Foam-Control R-SHIELD with opaque polyethylene film, tarps, or similar material.

Termite Resistant - Perform Guard®.

Foam plastic insulations have been shown to become termite infested under certain exposure conditions. Foam-Control R-SHIELD with Perform Guard® provides resistance to termite infestation. Please review literature on Foam-Control R-SHIELD with Perform Guard for complete information.

Resistance to Mold and Mildew.

Foam-Control R-SHIELD will not decompose and will not support mold or mildew growth. Foam-Control R-SHIELD provides no nutrient value to plants or animals.

Adhesives, Coatings, and Chemicals.

Solvents which attack Foam-Control R-SHIELD include esters, ketones, ethers, aromatic, and aliphatic hydrocarbons and their emulsions, among others. If Foam-Control R-SHIELD is to be placed in contact with materials (or their vapors) of unknown composition, pretest for compatibility at maximum exposure temperature.

Do not install or use Foam-Control R-SHIELD with coal tar pitch, highly solvent-extended mastics, or solvent-based adhesives without adequate separation.

Warranty.

Foam-Control R-SHIELD Licensees offer a product warranty ensuring thermal performance, physical properties, and termite resistance.



**MOLDED
PRODUCTS**

A Division of Atlas Roofing Corporation

For further information contact us:

Phone: (800) 277-0967

www.atlasfoamcontrol.com



Foam-Control products are manufactured by AFM Corporation licensees.

Copyright © 2020 AFM Corporation. All rights reserved. Printed in USA. Foam-Control, Perform Guard, and R-SHIELD are registered trademarks of AFM Corporation, Lakeville, MN. The Foam-Control R-Shield logo is a trademark of AFM Corporation, Lakeville, MN.

UL logo is a registered trademark of UL LLC. USGBC logo is a registered trademark of U.S. Green Building Council.

RS02-01/20



www.foam-control.com

**AIR BARRIER &
WEATHER RESISTIVE
INSULATION**